




# Dual-Slot Battery Charger for the C3A

---

## Charging Station


The dual-slot charger can charge up to two C3A batteries at the same time. Two independent LEDs indicate the charging status of each one: solid red means charging and solid green means fully charged.





# Long-Lasting Protection

Swap out the rechargeable battery from the C3A and power it up again in seconds. Enjoy months of power and protection per charge!



# Specifications CS-CMT-CHARGER-A / DDC-09FC-BATBK

## External Adapter Input & Output Characteristics

Input Voltages	AC 100V~240V 50Hz/60Hz
DC Output Voltage	5.0V
Output Current	1.0A/Slot
Charging Time	Approx. 8 Hours with 5V/2A Adapter and Standard Cable

## General

Charging Method	Constant Current & Voltage
Applicable Battery	EZVIZ 5,500 mAh Battery (For C3A)
Product Dimensions	98.4 x 59.3 x 52 mm (3.87 x 2.33 x 2.04 inch)
Package Dimensions	105 x 68 x 142 mm (4.13 x 2.68 x 5.59 inch)

## Package Contents:

- Charger
- Quick Start Guide

## Operating Environment

- Operating Temperature: -10°C ~ 45°C (14°F ~113 °F)
- Storage Temperature: -20°C ~ 70°C (-4°F ~158 °F)
- Operating Humidity: 10%~90%RH (Condensation: Not Required)
- Storage Humidity: 10%~95%RH (Condensation: Not Required)
- Operating Altitude: 0 ~5,000m

## Certifications

CE / FCC / IC

Specifications are subject to change without notice. EZVIZ is a registered trademark of Hangzhou EZVIZ Network Co., Ltd.  
Other brands and product names are trademarks or registered trademarks of their respective holders.